

SAFETY & SECURITY FILMS

	% Visible Light Transmission	% Total Solar Transmission	% Total Solar Reflectance	% Total Solar Absorbance	% Visible Light Reflectance INT/EXT	Winter U-Value	% Ultraviolet Protection (wavelengths 300-380nm)	% Glare Reduction	Shading Coefficient	% Solar Heat Gain Coefficient (SHGC)	% Total Solar Energy Rejection (TSER)
Clear Series											
2M	89	83	8	9	9/9	1.07	94	1	0.99	0.86	14
4M	89	82	8	10	9/9	1.07	99	1	0.98	0.85	15
7M	89	82	8	10	9/9	1.07	99	1	0.97	0.85	15
8M	88	81	9	10	10/10	1.06	99	2	0.96	0.84	16
13M	88	80	9	11	10/10	1.06	99	2	0.96	0.83	17
Symmetry™ Series (Dual-Reflective, Neutral)											
5M Symmetry 25	18	18	35	47	14/36	0.90	>99	80	0.35	0.31	69
9M Symmetry 25	18	18	35	47	14/36	0.90	>99	80	0.35	0.30	70
5M Symmetry 15	13	14	40	46	12/42	0.91	>99	86	0.30	0.26	74
9M Symmetry 15	13	14	40	46	13/42	0.91	>99	86	0.31	0.27	73
Silver Series (Reflective, Silver)											
5M Silver 20	13	10	56	34	65/62	0.87	>99	86	0.21	0.19	81
9M Silver 20	13	10	55	35	65/61	0.87	>99	86	0.22	0.19	81
Anti-Graffiti Series											
4M Anti-Graffiti	89	83	9	8	10/10	1.04	89	1	0.98	0.85	15
6M Anti-Graffiti	89	82	9	9	10/10	1.04	90	1	0.98	0.85	15