



Specialty

ARCHITECTURAL WINDOW FILMS

SunTek
WINDOW FILMS

SunTek specialty films range from subtle to dramatic and can be used on interior or exterior glass to decoratively enhance privacy.

Specialty designed for both Residential and Commercial applications

Specialty

ARCHITECTURAL WINDOW FILMS by SunTek®

BENEFITS

- Series of films that offer a combination of privacy, protection and solar performance
- Can be custom cut to achieve a specific or decorative look
- Helps block the sun's damaging UV rays
- Manufacturer's limited warranty*
* Certain restrictions apply; see an authorized dealer for manufacturer's limited warranty details.



HIGH-TECH INNOVATION

Technology driven systems producing an industry-leading, proprietary process.



A PRICE YOU CAN AFFORD

Innovative and efficient manufacturing delivering lower costs.



EXCEPTIONAL QUALITY

High-quality raw materials converted to meet industry standards.

Specialty Series

PERFORMANCE DATA	Black Out	DRMPS-7	DRMDS-7	LRDS-10	4M Anti-Graffiti	6M Anti-Graffiti
Visible Light Transmission	0%	7%	7%	7%	89%	89%
Total Solar Transmission	0%	8%	8%	14%	83%	82%
Total Solar Reflectance	6%	56%	57%	26%	9%	9%
Total Solar Absorbance	94%	36%	35%	60%	8%	9%
Visible Light Reflectance						
Interior	7%	17%	17%	11%	10%	10%
Exterior	6%	61%	62%	11%	10%	10%
Winter U-Value	1.05	0.89	0.93	0.95	1.04	1.04
Ultraviolet (UV) Protection*	>99%	99%	99%	>99%	89%	90%
Glare Reduction	>99%	92%	92%	92%	1%	1%
Shading Coefficient	0.35	0.19	0.20	0.35	0.98	0.98
Solar Heat Gain Coefficient	0.30	0.17	0.17	0.31	0.85	0.85
Total Solar Energy Rejection	70%	83%	83%	69%	15%	15%

Additional Specialty Products Available: 2M White Matte, White Out**, Crystal PET** and Crystal Vinyl****

**There is no accepted method for measuring the solar performance properties of opaque, patterned or translucent products. Any variation in appearance will be subject to normal manufacturing variances.

*Wavelengths 300-380nm. Data captured using National Fenestration Rating Council's (NFRC) guidelines on single pane, nominal 1/8 inch (3mm) clear glass. Reported values are taken from representative product samples and are subject to normal manufacturing variances. Actual performance will vary based on a number of factors, including glass type and properties.



345 Beaver Creek Drive
Martinsville, VA 24112

TEL 276.632.4991
FAX 276.632.0173

suntekfilms.com

©2020 Eastman Performance Films, LLC. Product brands referenced herein with a ™ or ® symbol are trademarks of Eastman Chemical Company or its subsidiaries. All other trademarks are the property of their respective owners. All rights reserved. No liability is accepted for errors. 02/20 GMN 50185510