

Avery Dennison® NR Series Automotive Window Films

Superb Solar Protection and Stylish Look

Avery Dennison® NR Series automotive window films are specially designed for keeping car interiors safer from the harmful sun.

The combination of advanced UV stable embedded dye film with additional UV absorbing pressure sensitive adhesive, provides excellent UV block protection of the vehicle interior and passengers.

Features and Benefits

- Exceptional aesthetics, no-fade warm graphite color.
- Great heat rejection and up to 94% glare reduction, with minimal reflective effect.
- Blocks 99% of harmful UV.
- Designed for easy and professional installation.
- Stylish car upgrade without any signal interference (metal free).



Series	NR Non-Reflective
Technology	UV Stable Dye Metal-Free
Color Tone	Warm Graphite
Construction	2-Ply Weatherable
Thickness	1.5 Mil
Warranty	Lifetime, Limited Non-Transferable ¹
Color Stable	Yes

¹ For information on warranty terms, exclusions and certain limitations that apply please see the applicable product data sheets and other literature and bulletins on our website: graphics.averydennison.com

Optical & Solar Properties²

Film		Ultra-violet Block	Visible Light		Glare Reduction	SIRR ³	IRER ⁴	Shading Coefficient	Total Solar Energy			
			Transmitted	Reflected (Exterior)					Reflected	Transmitted	Absorbed	Rejected
NR 05	R058P0G	>99%	5%	7%	94%	34%	27%	0.62	7%	39%	54%	45%
NR 20	R058P6G	>99%	20%	7%	77%	33%	26%	0.67	8%	44%	48%	42%
NR 35	R058P5G	>99%	37%	8%	58%	33%	26%	0.71	8%	51%	41%	38%
NR 50	R058P7G	>99%	48%	8%	45%	32%	25%	0.77	8%	56%	36%	33%

Warm Graphite Appearance

A warm metal-free graphite tone of NR Series automotive window films are offered in four VLT levels.



This image has been simulated and is not actual product comparison.

Ease Of Installation

NR Series automotive window films have excellent professional installer features including optimal heat-shrink capabilities that tack fast, for a durable and secure fit as well as easy clean removal for effortless adjustments.

²Performance results are calculated on 1/4" (6mm) clear glass using NFRC methodology and LBNL Window 5.2 software, and are subject to variations in process conditions within industry standards.

³SIRR - Selective InfraRed Rejection: the percentage of IR radiation that is not directly transmitted through a glazing system. Calculated as %SIRR = 100% - % Transmission (@ 780-2500nm).

⁴IRER - InfraRed Energy Rejection: the percentage of Near Infrared Energy Rejection as measured between 780-2500nm. Calculated as the TSER over 780-2500nm: %IRER = 100% - 100*SHGC (@ 780-2500nm).

⁵Colors and tinting level are an approximate match. For a true color reference, please refer to the actual film sample.

All statements, technical information and recommendations about Avery Dennison products are based upon tests and information believed to be reliable but do not constitute a guarantee or warranty of any kind. All Avery Dennison products are sold with the understanding that Purchaser has independently determined the suitability of such products for its intended and other purposes.

A444632 07/2021



For information on warranty terms, exclusions and certain limitations that apply please see our website: graphics.averydennison.com. All statements, technical information and recommendations about Avery Dennison products are based upon tests and information believed to be reliable but do not constitute a guarantee or warranty of any kind. All Avery Dennison products are sold with the understanding that the Purchaser has independently determined the suitability of such products for its intended and other purposes.

©2020 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.